


■ **Kilkenny Tweed** Grade 2V or E
Vinyl




**WORKING
FOR
YOU**




NIGHTSHADE
VKNE




GINGER
VKGR




BITTERSWEET
VKBT




STONE
VKSE




APPLE TORTE
VKAE




CLAY POT
VKCT




SISAL
VKSL




KHAKI
VKKI




SLATE
VKST




ICE
VKIE



CELERY
VKCY





SPRUCE
VKSC



NIGHTSHADE
VKNE

■ Specification Information

Description	Kilkenny Tweed
Grade	2V or E
Content	100% Vinyl Surface, Hi-Loft ² Backing
Width	54"
Weight	32 oz.
Finishes & Treatments	PERMABLOK ³ ® Advanced Vinyl Protection Antistatic Slip Finish Cold Crack - 20° F (-28.9° C) Heat Sealable Mildew Resistant Backing and Face Oil Resistant Sulfide Stain Resistant/All Colors UV Stabilized Pigments
Performance	
 Abrasion	Superior Abrasion Resistance 75,000 Cycles – Wyzenbeek/CFFA- I (Federal Standard 191A – Method 5304). Abrasion resistance is the surface wear of a fabric caused by rubbing and contact with another fabric.
 Flame Resistance	Passes California Technical Bulletin # 117 Section E – Class I. Flame resistance is the measurement of a fabric's performance when it is exposed to specific sources of ignition.

Colors may vary slightly between dye lots.

Permablok³® is a registered trademark of Spradling International, Inc.

KI and Working For You are registered trademarks of Krueger International, Inc.

© 2007 KI Litho in USA KI-32418/HC/EWB/1107

